

TUBE 200

Light. Line. Architecture

Uniform light output
Visual comfort
High energy efficiency
Discreet presence
Strong effect

BUCK GMBH
TAUNUSTOR 1
60310 FRANKFURT AM MAIN
OFFICE@BUCKLICHT.DE
WWW.BUCKLICHT.DE

COPYRIGHT © 2025 BUCK

BUCK

WWW.BUCKLIGHTING

Light in its purest form





Luminaire of opal PMMA provides uniforme defused light
Glare illumination control UGR <22



TEHNICAL DATA

Dimensions A/Ø	1300, 1900, 2500, 3600 / 200
Ingress protection rating	IP42
Weight	3 / 4.5 / 6 / 9kg
Optics	Opal PMMA
Luminaire luminous flux (ta=25°)	6176 / 9264 / 12352 / 18528lm
Total power	127W
LED	High efficiency (145+ lm/W)
LED SERVICE LIFE	60000h L80B10
Light colour temperature /CRI	4000K / >80
SDCM3	
UGR	<22
Power supply	220-240 V 50-60 Hz
CONTROL GEAR	ECG, DALI

Diferent light color temperatures / CR>90 available on request





Tunable white on request

Seamlessly transitions from warm 2700K to cool 6500K light, supports natural circadian rhythms and enhances comfort throughout the day. Perfect for offices, hospitality, healthcare and residential environments where both performance and atmosphere matter.



APPLICATION

General illumination appropriate for voluminous spaces in public and commercial interiors

- Office spaces
- Hospitality and retail
- Museums and galleries



A Silent Presence in Space